

## Coverage

Approximate sq.ft. Coverage per #1 unit (5 kg) of Gripoxy grout

Tiles Size X Thickness	Joint Width							
	In mm	2mm	3mm	4mm	6mm	8mm	10mm	12mm
100x100x3	264	177	133	90	68	55	46	
150x150x4	296	198	149	100	75	61	51	
200x150x5	269	181	136	91	69	55	46	
150x300x6	263	175	132	88	66	53	44	
300x300x6	394	263	198	132	100	80	67	
450x300x7	405	270	202	135	101	81	68	
600x450x8	506	337	253	169	127	101	85	
600x600x8	591	394	295	197	148	119	99	
600x900x11	515	343	258	171	129	103	86	
900x900x12	590	393	295	197	148	118	99	

## Approximate sq.ft. Coverage for glass mosaic

Tile Size	Joint Width	Joint Depth
20mmx20mm	1.5mm	2mm
<b>Coverage 64 sq.ft. to 72 sq.ft. per #1 unit (5kg)</b>		

## Note

- Quantities shown are approximate and are given for estimating purpose only. Actual job site coverage may be vary.
- It is always good practice when calculating coverage to allow for 10-15 % additional materials for wastage and spoilage.
- Verify actual appearance and compatibility with a test area before installation commences.
- Actual shade and texture will depend on job site conditions.
- There may be a shade variation in different batches. It is advised to mix grout from different batches to get uniform color.

\*Colour shown in this shade card are for indication purpose only, Slight variation may occur.

## • Gripoxy Grout For Floor & Wall

Gripoxy grout for floor & wall is an epoxy grout specifically designed to enhance aesthetics and performance. It is suitable for use with ceramic tiles, vitrified tiles, glass mosaic tiles, designer tiles and natural stone

## • Application

- Kitchen
- Swimming Pool
- Bathroom
- Hospital
- Restaurant
- Laboratories

## • Advantages

- Excellent waterproof and durable finish
- Highly chemical and acid resistant
- Non cracking and powdering
- High bonding and durability
- Easy to install and clean
- Stain free

## Packaging

Factory proportioned kit consisting of three conveniently packed components - Resin (PART-A), Hardner (PART-B), Filler Powder (PART-C).

Pack Size	Resin (Part-A)	Hardner (Part-B)	Filler Powder (Part-C)
1 Kg.	200 gm	100 gm	700 gm
5 Kg.	1 kg	500 gm	3.5 kg.

## Color

Available in plain color and 3 finishes - silver, gold and copper



## Advantages

Stain free color fast, easy to install and clean, water cleanable, non creaking or powdering anti bacterial and anti furgial chemical & temperature resistance, easy maintenance, available in range, hard & durable joints, high strength & variably waterproof & durable joints.

## Recommended For

Ceramic floor & wall tiles quarry tiles, marble, mosaics, stone, porcelain tiles / vitrified tiles, pavers, metal tiles, natural stones synthetic & engineered stones, agglomerate stones.

## Packing

1 Kg., 5 Kg. and Bucket



Mfg. & Mktg. by:

## GRIFFON CHEMICO INDUSTRIES

Plot No.7, Dharma Bhoomi Industrial Estate, opp. Shiv Park, Jetpar Road, Village – Pipali, Sub District & District – Morbi, 363 642, Gujarat, (INDIA).

**Contact.**  
+91 90236 94194

**Email.**  
info@griffonchemico.com  
Sales@griffonchemico.com

**Web.**  
www.griffonchemico.com

# EPOXY GROUT

ADDING TOUCH OF QUALITY,  
WE CARE FOR YOUR DREAMS



ISO 9001:2015 CERTIFIED COMPANY

## EPOXY GROUT SOLID COLOR

